



# CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

## COLOUR INTENSIFIER TECHNICAL DATA SHEET REF: 13/5/1/.5

### LTP COLOUR INTENSIFIER

#### Colour Enhancing Tile Sealer

##### For Interior & Exterior use

Suitable for slate, natural stone, tumbled marble, travertine, terracotta, quarry, terrazzo and sandstone.

Provides enhanced matt finish. For use on wall and floor surfaces. Strongly protects against water, oil, grease and dirt. Allows surface to breathe.

#### Directions for use:

This sealer is very difficult to remove once hardened. Do not over apply. The surface to be treated must be completely clean, dry and free from contamination. If necessary, first clean floor with LTP Grimex and allow to dry thoroughly. Apply this sealer thinly and uniformly with a cloth, brush or sponge and allow to penetrate for approximately 15-30 minutes before wiping over with a clean dry fluff-free cloth to remove all and any excess which may remain on the surface. N.B. The surface must retain a matt finish after treatment. Any excess left on the surface could oxidise to form an unsightly gloss varnish. For stronger colour enhancement and in the case of more absorbent surfaces, further coats may be applied. Allow at least 30-60 minutes from application of previous coat before applying further coat. Do not apply in direct sunlight or in a temperature exceeding 25 degrees C. Beware of application upon floors with underfloor heating as the product may dry prematurely. If you are unsure of correct application methods, test on an inconspicuous area, prior to general application.

#### Health & Safety:

**Contains: White Spirit (naphtha petroleum, hydrodesulphurised heavy (<0.1% benzene)).**  
**FLAMMABLE. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.**  
**Harmful: may cause lung damage if swallowed.**  
**Repeated exposure may cause skin dryness or cracking.**

Keep out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves and goggles. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.



**VOC STATEMENT**  
EU Limit value for this product  
(Cat A/h) 750g/L (2010)  
This Product contains max  
749g/L VOC

UN1993

#### Coverage:

Per 10m<sup>2</sup>

Lower porosity floors

Higher porosity floors

-approximately 1-2 litres

-approximately 3-4 litres

#### Storage information:

Store in a cool, dry, frost free environment

#### Maintenance:

Routinely sweep the floor and wash with LTP Waxwash. Clean walls and work surfaces with LTP Stonewash spray. For further information refer to the technical data sheet.



*This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area*

*for beautiful surfaces we have the solutions...*

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

July 2011

