



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

STONE OIL TECHNICAL DATA SHEET REF: 26/5/1

LTP STONE OIL

**Oil Based Pre-Polished Sealer
For Interior & Exterior use
Suitable for porous stone and terracotta.**

Easy to apply oil based impregnating sealer ideal for low porosity stone & terracotta. Enhances the colour and texture of floors. Offers good mechanical strength once cured.

Directions for use

Shake well.
Ensure surface to be treated is completely dry and free from contaminants which may prevent LTP Stone Oil from properly curing. Apply by brush or clean fluff-free cloth depending on the required application. Please note more porous floors may require more than one application, remove any excess sealer that has not been fully absorbed within 1 hour. Leave to cure for a minimum of 24 hours before finishing the surface with LTP Clear Wax, LTP Antique Wax, LTP Ironwax Satin or LTP Ironwax Gloss.

Important: If using this product outside finish with a coat of LTP Mattstone to offer extra protection. Used cloths should be burnt after use as they may spontaneously combust.

Coverage

per 10m²
Lower porosity floors – approximately 1 litre
Medium porosity floors – approximately 2 litres

Maintenance

For floors finished with LTP Ironwax Satin or Gloss. Routinely sweep the floor. Use LTP Floorshine to clean and protect the floor. In areas where the seal becomes worn, apply more sealer. On floors finished with LTP Clear Wax or LTP Antique Wax use LTP Waxwash. At some stage, complete renovation of the seal may be desired. In this case use LTP Grimex to strip the surface before re-sealing.

Storage information

Store in a cool, dry, frost-free environment.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN
T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

January 2013

Notes:

NB. Allow good ventilation during application. LTP Stone Oil may cure more rapidly in dry or higher temperature conditions. Avoid working in direct sunlight; rapid oxidation may inhibit effectiveness of the product. Not suitable for older floors that have no damp proof course.

Health & Safety

**Contains: White Spirit (naphtha (petroleum), hydrodesulphurised heavy (<0.1% benzene)).
Toxic to aquatic life with long lasting effects.
May be fatal if swallowed and enters airways.**

Keep away from food, drink and animal feeding stuffs. Keep out of the reach of children. Store locked up. IF SWALLOWED: do NOT induce vomiting. Get immediate medical advice/attention. Avoid release to the environment. Avoid breathing vapours. Dispose of contents/container in accordance with local authority requirements.



Danger

VOC STATEMENT

EU Limit value for this product
(Cat A/h) 750g/L (2010)
This product contains max 419g/L VOC

UN 1263

EC Label EC No 1272/2008

