



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

STONEFOAM TECHNICAL DATA SHEET REF: 32/25

LTP STONEFOAM

- Ideal for stone fireplaces and worktops
- Easy to apply, fast acting formula
- Removes all types of dirt and grease
- Suitable for polished and unpolished stone
- Internal and external use

LTP Stone Foam cleaner deep cleans surfaces to remove all types of dirt and grease. Ideal for removing build up of wax and aftercare product. Use as an intensive cleaner for conditioning new surfaces before sealing or as an intensive cleaner for renovating existing surfaces. Suitable for polished and unpolished natural and artificial stone including limestone, granite, marble, travertine, slate, sandstone, quartz, terrazzo, basalt, concrete and all other types of masonry surface.

Suitable for internal and external use.

Directions for use:

Preparation:

Areas to be treated must be free from dust before application. Mask and protect surfaces that are not to be treated.

Honed, Smooth, Polished, Rough Cut, tumbled, textured or riven surfaces:

Shake well. Hold can 15-20 cm from the surface and spray in a sweeping motion. Allow the foam to dissolve. This will take 5 – 10 minutes. Add a little water and agitate with a white emulsifying pad or similar mild abrasive pad, cloth or brush to help release the ground in dirt and grime. Rinse well with plenty of water and a sponge making sure to change rinsing water regularly.

On extremely dirty surfaces this process may need to be repeated.

Health & Safety:

Extremely flammable. Irritating eyes and skin. Keep out of reach of children. Keep away from sources of ignition- No smoking. Do not breathe vapour/spray. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves. Use only in well-ventilated areas. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.



USE ONLY AS DIRECTED

UN 1950

Coverage:

5 - 10 m² depending upon the porosity and the number of coats required.

Storage information:

Store in a cool, dry, frost free environment.

Notes:

Do not spray on to painted, acrylic or stained surfaces such as cabinets and stained timber skirting boards. Mask and protect these surfaces before application. Use only in open or well ventilated areas. It is recommended that a suitable respiratory mask be worn at all times. Overspray on some surfaces, may in some cases cause damage; in which case wipe up and rinse immediately with clean water. Always test the product on an inconspicuous area for suitability before general application.

Shake can well before use.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

Jul-11

