



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

STONESEAL TECHNICAL DATA SHEET REF: 31/25

LTP STONESEAL

- Ideal for stone fireplaces and worktops
- Easy to apply, quick drying spray-on formula
- Long lasting protection against all types of dirt and grease
- Suitable for polished and unpolished stone
- Internal and external use

Forms a colourless barrier and helps to protect porous stone surfaces from water, dirt, oil, grease, soot and lime scale, making treated surfaces easier to keep clean. Protection for polished and unpolished natural and artificial stone including limestone, marble, travertine, slate, sandstone, quartz, terrazzo, basalt, concrete and all other types of masonry surface.

Suitable for internal and external use.

Directions for use:

Always use a mask. Use in well ventilated areas.

Preparation:

Areas to be treated must be cleaned. Older contaminated and dirty stone surfaces should be cleaned with LTP Stone Foam Intensive Cleaner and then rinsed thoroughly. Newly installed surfaces should be clean and free from dust before application.

Rough Cut, tumbled, textured or riven surfaces:

Shake can well. Hold can 15-20 cm from the surface and spray in a sweeping motion. Touch dry within 5 minutes. Test area 30 minutes after application with a little water, if the water is absorbed, a second or even third coat may be required to obtain maximum performance. A 2-3 hour curing time is recommended upon completion before allowing traffic.

Honed, smooth and polished surfaces:

Shake can well. Hold can 15 -20 cm from the surface and spray in a sweeping motion. Leave for up to 5 minutes and then remove visible excess with an absorbent cloth. Finish after removal of excess by buffing with soft lint free cloth or machine with buffing pad. Do not allow residues to dry on the surface.

Shake can well before use.

Health & Safety:

Extremely flammable. Irritating to skin. Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness

Keep out of reach of children. Keep away from sources of ignition. No smoking. Do not breathe vapour/spray. Avoid contact with skin and eyes. Do not empty into drains. Use only in well-ventilated areas. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.



USE ONLY AS DIRECTED

UN 1950

Coverage:

5 - 10 m² depending upon the porosity and the number of coats required.

Storage information:

Store in a cool, dry, frost free environment

Maintenance:

Do not use harsh abrasive cleaning agents. Clean treated areas with LTP Stone Care Maintenance Cleaner. In some instances it may be necessary to use a stronger cleaner to remove stubborn surface marks, in which use LTP Stone Foam Intensive and then reseal.

Notes:

Do not spray on to painted, acrylic or stained surfaces such as cabinets and stained timber skirting boards. Mask and protect these surfaces before application. Use only in open or well ventilated areas. Open windows and if possible use fans to circulate air. It is recommended that a suitable respiratory mask be worn at all times. Overspray on some surfaces may in some cases leave a slight residue, in which case wipe up any excess within 5 minutes. Stubborn residues left on the surface can be removed with the application of more LTP Stone Sealer which should then be buffed off immediately. For wet areas including shower enclosures and wet rooms allow the sealer to cure for a minimum of 24 hours before use. Always test the product on an inconspicuous area for suitability before general application.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

Jul-11